HRS Connectors for Human Machine Interface

Hirose Electric, as a world leader in the connectivity industry, has been developed a broad innovative electronic connectors over the years since its founding.

Please visit our Web site for details of the listed products as well as other related product lines.

Small Interface Connectors



Handy Terminal



ZX360 Series USB3.0 Connector



TM11R Series RJ-45 Modula Jack supporting CAT5



UX Series USB2.0, Mini-USB Connectors




IX Series High Speed Transmission Compact and Rugged I/O Connector




DH Series 1mm Pitch, Small Size, High Speed Transmission

Small, Low Profile Coaxial Connectors



U.FL Series 1.9-2.4mm Height

FPC/FFC Connectors



W.FL Series 1.18-1.65mm Height

FH41 Series

0.5mm Pitch,

Supports Shielded FFC



MS-180 Series **Check Terminal** 0.85mm Height




MS-156 Series Check Terminal 1.35mm Height



FH52E Series 0.5mm Pitch, 2mm Height



FH55 Series 0.5mm Pitch, High Speed Transmission



FH28 Series 0.5mm Pitch, Robust



FH19C/FH19SC Series 0.5mm Pitch, 0.9mm Height



FH48 Series 0.5mm Pitch, Supports Shielded FFC



Embedded **Display Panels**

*Specifications herein are subject to change without notice. Contact Hirose for the latest specifications, drawings, and availabilities.

WireBoard Connectors



DF57H Series 1.2mm Pitch, Low Profile




DF50A Series 1mm Pitch, Single-row Positive Lock

Low Profile BoardBoard Connectors



DF22 Series Internal High Current Connectors for Power Supply



DF50 Series 1mm Pitch, Double-row Positive Lock



DF61Y Series 2mm Pitch, High current capability: 4A



DF62 Series Slim In-Line Connectors



DF12 Series 0.5mm Pitch, 3-5mm Height Parallel Board Connections



FX18 Series 0.8mm Pitch 10-45mm Height High Speed Transmission



FX8/FX8C Series 0.6mm Pitch 316mm Height High Speed Transmission





FX10 Series 0.5mm Pitch, 4-13mm Height, Floating structure High Speed Transmission



FX20 Series 0.5mm Pitch, 15-30mm Height Floating Structure

FX23 Series

0.5mm Pitch

1530mm Height







Floating Structure High Speed Transmission



FX15 Series 1mm Pitch, Support LVDS/TMDS



FX16 Series 0.5mm Pitch, Support 5.7Gbps



For more information about Hirose products: http://www.hirose.com					
[Japan]		TEL: +81-45-620-3491	[Malaysia]	(Penang)	TEL: +604-619-2564
[China]	(Shanghai)	TEL: +86-21-6391-3355	[Thailand]	(Bangkok)	TEL: +66-2-686-1255
	(Beijing)	TEL: +86-10-5165-9332	[USA]	(Chicago) (USA HQ)	TEL: +1-630-282-6700
	(Shenzhen)	TEL: +86-755-8207-0851		(San Jose)	TEL: +1-408-253-9640
[Hong Kong]	(Kowloon)	TEL: +852-2803-5338		(Detroit) (Automotive)	TEL: +1-734-542-9963
[Taiwan]	(Taipei)	TEL: +886-2-2555-7377	[The Netherlands]	(Amsterdam)	TEL: +31-20-6557460
[Korea]	(Siheung)	TEL: +82-31-496-7000 or 7124	[Germany]	(Stuttgart)	TEL: +49-711-4560021
[Singapore]	(Anson Road)	TEL: +65-6324-6113		(Nuremberg)	TEL: +49-911-32688963
[India]	(Delhi)	TEL: +91-12-660-8018		(Hanover)	TEL: +49-511-97826130
	(Bangalore)	TEL: +91-80-4120-1907	[France]	(Paris)	TEL: +33-1-85764886
			[UK]	(Milton Keynes)	TEL: +44-1908-202050

*Specifications herein are subject to change without notice. <u>Contact Hirose for the latest</u> specifications, drawings, and availabilities. HIROSE ELECTRIC CO., LTD. © 2016 HIROSE ELECTRIC CO., LTD. All rights reserved.

Oct. 18, 2016