# **HRS** Connectors for Patient Monitor Equipment

The products depicted in this brochure are a sampling of the many connector solutions manufactured by Hirose. Please visit our Web site for details of the listed products as well as other related product lines.

# **Patient Monitor Equipment**



### Circular I/O

**HR30** Series



Push-pull lock of IP68 Contact position: 3, 6, 10, 12pos. Rated current: 5A Max. (3pos.) Rated Voltage: 100V AC Max. Applicable wire: 20-26 AWG wire

#### **RP13 Series**



Push-pull lock Contact position: 13, 15, 20pos. Rated current: 2A Max. RatedVoltage: 300V AC Applicable wire: 18-28 AWG wire

#### Rectangle I / O **RP34 Series**




Low profile, Power I/O Contact position: 2, 3, 4pos. Rated current: 5A Max. (2, 3pos.) Rated Voltage: 30V AC, 42V DC Applicable wire: 18-22 AWG wire

#### **GT17H Series**



Positive lock. USB signal transmission, High speed transmission (up to 1 +Gbps) Low profile, Space saving Rated Voltage: 250V AC

#### **B** to W Connector **DF57H Series**



Swing lock Mated height: 1.4mm Pitch: 1.2mm Contact position: 2-6pos. Rated current: 2.5A (2pos.) Applicable wire: AWG 28-34

#### **DF61Y Series**



ViSe lock Mated height: 2.0mm Pitch: 2.2mm Contact position: 2pos. Rated current: 4A Max. Applicable wire: AWG 24-28

# Mezzanine

## FX10 Series



FX11 Series

#### High speed transmission (10Gbps) Pitch: 0.5mm Stacking height: 4-13mm

High speed transmission

(10Gbps)

Pitch: 0.5mm

Stacking height:

#### **DF12 Series**



Pitch: 0.5mm Stacking height: 3-5mm

#### **ER8** Series



High speed transmission (10Gbps) Pitch: 0.8mm Stacking height: . 7-12mm

# **FPC / FFC Connection**




Bottom/Top,Vertical contact Pitch: 0.5mm Contact position: 6-60pos.



Bottom contact, Robust Pitch: 0.5mm, Height: 2.55mm Contact position :

10-80pos



2-3mm

		1 1 1 1
[Japan]		TEL: +81-45-620-3491
[China]	(Shanghai)	TEL: +86-21-6391-3355
	(Beijing)	TEL: +86-10-5165-9332
	(Shenzhen)	TEL: +86-755-8207-0851
[Hong Kong]	(Kowloon)	TEL: +852-2803-5338
[Taiwan]	(Taipei)	TEL: +886-2-2555-7377
[Korea]	(Siheung)	TEL: +82-31-496-7000
[Singapore]	(Anson Road)	TEL: +65-6324-6113
[India]	(Delhi)	TEL: +91-12-660-8018
	(Bangalore)	TEL: +91-80-4120-1907

[Malaysia] [Thailand] [USA]

[The Netherlands] [Germany]

[France] [UK]

(Penang) (Bangkok) (Chicago) (USA HQ) (San Jose) (Detroit) (Automotive) (Amsterdam) (Stuttgart) (Nuremberg) (Hanover) (Paris) (Milton Keynes)

TEL: +604-619-2564 TEL: +66-2-686-1255 TEL: +1-630-282-6700 TEL: +1-408-253-9640 TEL: +1-734-542-9963 TEL: +31-20-6557460 TEL: +49-711-456002-221 TEL: +49-911-326889-63 TEL: +49-511-978261-30 TEL: +33-1-85764886 TEL: +44-1908-202050

Specifications herein are subject to change without notice. Please contact Hirose for the latest specifications, drawings and availabilities.

© 2017 HIROSE ELECTRIC CO., LTD. All rights reserved. HIROSE ELECTRIC CO., LTD.