



3

Contactors

CF series

Multipole
AC power contactors
for 300 A or 600 A
with NO or NC
switching chambers

Flyer C60.en



More information
schaltbau.com

CF – Multipole AC power contactors

Schaltbau's new, highly modular CF series begins with a compact 3-pole AC power contactor for loads up to 600 A and 3000 V for inverter-fed alternating current drives with higher frequencies. One special feature are the newly developed switching chambers. These can be universally configured as NO, NC or in combination as a change-over.

An efficient electronic economy circuit reduces power consumption as well as heat loss and saves costs.

- Compact dimensions – high performance range: 3,000 Volt AC / 3x 600 Ampere, frequencies up to 400 Hertz
- Innovative application-dependent arc chamber design – configurable as NO, NC or changeover contact
- High thermal continuous current 300 amps or 600 amps through parallel connection of two main contacts each and a high rated short-time withstand current up to 4,000 amps

CF contactors can be adapted in many ways. The high variance makes the devices interesting for use in many different applications. The innovative switchgear is equally ideal for new projects and modernisation. They can successfully replace cam contactors that have proven themselves over many years. DC variants will follow.

- 4 auxiliary switches for diagnosis and switching status monitoring
- Low energy consumption and low heating thanks to sophisticated coil saving circuit

Ordering code

Example: **CFS3-15-12121200000N-AM-41**

Series, contact configuration

CFS1 / CFS2 / CFS3 1 / 2 / 3 pole AC contactor
CFW4 / CFW5 / CFW6 4 / 5 / 6 pole AC contactor

Nominal voltage U_n

15 / 30 1,500 V AC / 3,000 V AC

Version / 1x per main contact

1 / 2 NO / NO + insulating panel
3 / 4 NC / NC + insulating panel

Auxiliary switches, number / type

Number 1 / 2 / 3 / 4

S870 silver contacts – S870 gold contacts 1 / 2

Coil design

Monostable / monostable with control impulse M / N

Coil voltage U_s

24 V DC / 110 V DC A / C

Conventional thermal current I_{th} / 1x per main contact


300 A AC, $f \leq 400$ Hz: Plastic / metal extinguishing element 8 / 9

200 A AC, $f \leq 400$ Hz: Plastic / metal extinguishing element B / C

End insulating panel with/without Y / N

i Note: Series is being expanded. Further variants and configurations will follow.

CFS3 Dimension diagram, circuit diagram



Specifications

Series	CFxx-15-...	CFxx-30-...
Type of voltage	AC ($f < 400$ Hz)	
Main contacts	Number of / NO / NC 1 ... 6 / ☺ / ☹ Nominal voltage U_n 1,500 V 3,000 V Rated operating voltage U_e 1,500 V 3,000 V Rated insulation voltage U_{Nm} 3,000 V @ PD3, OV3 3,600 V @ PD3, OV2 Rated imp. withst. voltage U_{Ni}/U_{imp} 25 kV Pollution degree PD3 Overvoltage category OV3	
Conventional thermal current I_{th}	1 ... 3 Pole: 200 A / 300 A	
Component category	A2	
Rated short-time withstand current I_{cw}	4 kA / $T < 100$ ms	
Aux. contacts	Number, configuration	4x max. Snap-action switch S870
	Utilization category (EN 60947-5-1)	AC-15: 230 VAC/1.5 A; DC-13: 60 VDC/0.5 A
Magnetic drive	Coil voltage U_s	24 / 110 V DC
	Coil tolerance	0.7 ... 1.25 x U_s
Vibration / Shock	IEC 61373	Category 1, Class B
Mechanical endurance	1 million operating cycles	
Mounting position	horizontal, vertical (do not mount upside down)	
Temperatures	-40° C ... +70° C	
Weight	approx. 4 kg	